

AD302L

空気乾燥

品番: 40-1220




説明

装置を汚染し、結果に影響をもたらす水分を除去するAD302Lは、ラボにおける外部の空気供給源に取り付けることができる有用な機器です。軽量かつコンパクトで壁に取り付けられるAD302Lは幅を取らず、可動部品も少ないため、最小限のメンテナンスで済みます。



Generator Details

- ガスの種類: 空気
- 統合型コンプレッサ: 番号



主な機能

- クリーンで乾燥した空気を生成し、ガス発生器と機器への最適な供給を保証します
- 乾燥機は必要に応じて24時間年中無休で機能します
- ドライヤーは小規模な実験室に壁に取り付け可能
- 可動部品が少ないため、メンテナンスがほとんど不要で、発電機の寿命が長くなります
- 完全に無音の動作
- 最小限の設定が必要
- 12か月の包括的なオンサイト保証

技術仕様

	AD302L - 空気乾燥
ガスの種類	空気
最大ガス流量:	302L/min
ガス出口の設定:	1x 1/4" BSP Female
最低入口圧力:	100psi/6.9bar
最高入口圧力:	120psi/8.3bar
起動時間:	90 mins
消費電力:	8 - 19.2 W
電圧:	100 - 240 V
周波数:	50 / 60 Hz
電流:	0.8 A
認証:	CE
大きさ (高さx幅x奥行き) ミリメートル	910 x 160 x 471 mm
大きさ (高さx幅x奥行き) インチ	35.8 x 6.3 x 18.5 inches
装置の重量	20.5kg / 45.1lbs

[**PEAK** Protected]TM

Peak Scientific gas generators define the benchmark in reliability, convenience and performance in laboratories around the world, and come backed with a 12 month warranty. Beyond this period however you can ensure that your investment continues to be **[Protected]** by our comprehensive generator care cover.

Our world-class aftercare support packages deliver a program of scheduled preventative maintenance whilst giving you the reassurance of instant access to worldwide technical support and priority on-site response in the untimely event of a breakdown.

- For ordering parts visit: www.peakscientific.com/ordering/
- For service plans visit: www.peakscientific.com/service/service-plans/

Peak Scientific UK
Tel: +44 (0)141 812 8100
Fax: +44 (0)141 812 8200

Peak Scientific North America
Tel: +1-800-767-6532
Fax: +1-978-608-9503

Peak Scientific China
Tel: +86 21 5079 1190
Fax: +86 21 5079 1191
For a full list of our worldwide office locations, please visit:
Web: www.peakscientific.com
Email: discover@peakscientific.com

Peak Scientific's Quality Management System conforms to: ISO:9001

